

Bema surface mounted range of LED slim ceiling lights are a perfect fit for ambient lighting applications. The die cast aluminium housing is ideal for better thermal management. High lumen output & CCT options make this versatile for superior glare free indoor lighting solutions.

Product Description

- Luminaire made of die-cast aluminium for better thermal management.
- High efficiency diffuser for glare free, uniform light distribution.
- High lumen output, Integrated with 2835 LEDs.
- High PF constant current LED driver.
- Cable entries for through-wiring of mains supply cable
- Integral constant current power supply
- Suitable for operation on 240V, 50Hz single phase ac supply.
- Ordering guide : KL-7326-CCT (Colour Temperature)
- Available CCT : 3000K, 4000K, 6000K



Product Benefits

- Elegant homogeneous designs.
- Attractive high quality housing.
- Sturdy construction in order to maintain performance of the luminaire and to reduce maintenance costs.
- Quick & simple installation.
- Flexible deployment options with a wide spectrum of applications.

Area of Application

Corporate Offices, Malls, Restaurants, Receptions, Corridors, Commercial & Business Centers.

Available Finish

Epoxy polyester powder coating White / Black.





Technical Specifications

General

ID	: 7326
System Wattage	: 22W LED
Driver Integral	: Constant Current
Input Voltage	: 230-240Vac
Frequency	: 50-60Hz
Operating Voltage	: 100-240Vac
Operating Temperature	: -15°C~+50°C

Physical

Body	: Die-Cast Aluminium
Diffuser	: Translucent Polystyrene
Mounting	: Surface - Ceiling
Finish	: Powder coating White / Black

Light Source


Light Source	: SMD 2835
LED Lumens	: 2640 lm
CRI (Ra)	: >80
LED Colour Temperature	: 3000K / 4000K / 6000K

Driver


Power Supply	: Integral
Power Factor	: >0.9
THD	: <10%
Surge Protection	: 2.5KV
Efficiency	: >80%
Dimmable Options	: Triac / 1-10V / Dali

Optical Performance

Colour Temperature	: 3000K
Luminous flux	: 2046 lm
Beam Angle	: 120°



Light Distribution



Bema surface mounted range of LED slim ceiling lights are a perfect fit for ambient lighting applications. The die cast aluminium housing is ideal for better thermal management. High lumen output & CCT options make this versatile for superior glare free indoor lighting solutions.

Product Description

- Luminaire made of die-cast aluminium for better thermal management.
- High efficiency diffuser for glare free, uniform light distribution.
- High lumen output, Integrated with 2835 LEDs.
- High PF constant current LED driver.
- Cable entries for through-wiring of mains supply cable
- Integral constant current power supply
- Suitable for operation on 240V, 50Hz single phase ac supply.
- Ordering guide : KL-7327-CCT (Colour Temperature)
- Available CCT : 3000K, 4000K, 6000K



Product Benefits

- Elegant homogeneous designs.
- Attractive high quality housing.
- Sturdy construction in order to maintain performance of the luminaire and to reduce maintenance costs.
- Quick & simple installation.
- Flexible deployment options with a wide spectrum of applications.

Area of Application

Corporate Offices, Malls, Restaurants, Receptions, Corridors, Commercial & Business Centers.

Available Finish

Epoxy polyester powder coating White / Black.





Technical Specifications

General

ID	: 7327
System Wattage	: 36W LED
Driver Integral	: Constant Current
Input Voltage	: 230-240Vac
Frequency	: 50-60Hz
Operating Voltage	: 100-240Vac
Operating Temperature	: -15°C~+50°C

Physical

Body	: Die-Cast Aluminium
Diffuser	: Translucent Polystyrene
Mounting	: Surface - Ceiling
Finish	: Powder coating White / Black

Light Source


Light Source	: SMD 2835
LED Lumens	: 4320 lm
CRI (Ra)	: >80
LED Colour Temperature	: 3000K / 4000K / 6000K

Driver

Power Supply	: Integral
Power Factor	: >0.9
THD	: <10%
Surge Protection	: 2.5KV
Efficiency	: >80%
Dimmable Options	: Triac / 1-10V / Dali

Optical Performance

Colour Temperature	: 3000K
Luminous flux	: 3044 lm
Beam Angle	: 120°



Light Distribution

