


**LUMINAIRE PHOTOMETRIC TEST REPORT**

Test:U:230.65V I:0.0557A P:12.354W PF:0.9623 Freq:50.00Hz Lamp Flux:1631x1 lm		
NAME: CYLIN MINI	TYPE:CEILING LUMINAIRES	WEIGHT:
SPEC.:WW, CITIZEN, BA-40°	DIM.: Ø100 x 150	SERIAL No.:4896
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-3647	Imax (cd)	2551	S/MH (C0/180)	0.61
NOMINAL POWER (W)	12	LOR (%)	74.3	S/MH (C90/270)	0.61
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	1211.8	η UP, DN (C0-180)	0.0, 37.4
NOMINAL FLUX (lm)	1631	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 36.9
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	230	η down (%)	74.3	CIBSE SHR MAX	0.60



**C Range: 0 - 360DEG**  
**C Interval: 10.0DEG**  
**Test Speed: HIGH**  
**Temperature: 25.3DEG**  
**Operators: K-LITE**  
**Test Date: 07 September 2022**

**γ Range: 0 - 90DEG**  
**γ Interval: 1.0DEG**  
**Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.00.417**  
**Humidity: 65.0%**  
**Test Distance: 1.852m [K=1.0000]**  
**Remarks:**