


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.01V I:0.0751A P:17.251W PF:0.9730 Freq:49.99Hz Lamp Flux:2087.4x1 lm		
NAME: MUSHROOM	TYPE: BOLLARDS	WEIGHT:
SPEC.: CW, NICHIA	DIM.: Ø168 x 503	SERIAL No.: 2184
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-5583	Imax (cd)	523.3	S/MH (C0/180)	1.19
NOMINAL POWER (W)	16	LOR (%)	58.1	S/MH (C90/270)	1.17
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	1213.2	η UP, DN (C0-180)	0.0, 29.0
NOMINAL FLUX (lm)	2087.4	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 29.2
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	230	η down (%)	58.1	CIBSE SHR MAX	1.30



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: K-LITE
 Test Date: 28 October 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
 Humidity: 65.0%
 Test Distance: 1.825m [K=1.0000]
 Remarks: