


### LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.62V I:0.0548A P:5.8465W PF:0.4628 Freq:50.00Hz Lamp Flux:546x1 lm		
NAME: SLEEK PLATINA MICRO	TYPE: RECESSED CEILING	WEIGHT:
SPEC.: CW, CREE	DIM.: Ø33 x 91	SERIAL No.: 4482
MFR.: K-LITE	SUR.:	Shielding Angle: 15°

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-3338	Imax (cd)	2331	S/MH (C0/180)	0.33
NOMINAL POWER (W)	6	LOR (%)	49.6	S/MH (C90/270)	0.29
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	270.86	η UP, DN (C0-180)	0.0, 25.3
NOMINAL FLUX (lm)	546	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 24.3
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	230	η down (%)	49.6	CIBSE SHR MAX	1.00



**C Range: 0 - 360DEG**  
**C Interval: 10.0DEG**  
**Test Speed: HIGH**  
**Temperature: 25.3DEG**  
**Operators: K-LITE**  
**Test Date: 28 April 2022**

**γ Range: 0 - 90DEG**  
**γ Interval: 1.0DEG**  
**Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.00.417**  
**Humidity: 65.0%**  
**Test Distance: 1.825m [K=1.0000]**  
**Remarks:**