


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.43V I:0.0927A P:21.008W PF:0.9833 Freq:49.99Hz Lamp Flux:2812x1 lm		
NAME: HERA	TYPE: RECESSED CEILING	WEIGHT:
SPEC.: NW, CITIZEN	DIM.: Ø140 x 65	SERIAL No.: 1314
MFR.: K-LITE	SUR.:	Shielding Angle: 60°

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 92.70 lm/W
MODEL	KL-3352	I _{max} (cd)	1694	S/MH (C0/180)	1.00	
NOMINAL POWER (W)	20	LOR (%)	69.3	S/MH (C90/270)	1.00	
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	1947.5	η UP, DN (C0-180)	0.0, 34.8	
NOMINAL FLUX (lm)	2812	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 34.4	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.00	
TEST VOLTAGE (V)	230	η down (%)	69.3	CIBSE SHR MAX	1.05	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: K-LITE
 Test Date: 18 May 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
 Humidity: 65.0%
 Test Distance: 1.825m [K=1.0000]
 Remarks: