
LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.52V I:0.0848A P:17.678W PF:0.9039 Freq:49.99Hz Lamp Flux:2090.5x1 lm		
NAME: ISHA - SQUARE	TYPE:RECESSED CEILING	WEIGHT:
SPEC.:CW, EPISTAR	DIM.: Sq.130 x 27	SERIAL No.:1649
MFR.: K-LITE	SUR.:	Shielding Angle:120°


DATA OF LAMP		PHOTOMETRIC DATA		Eff: 99.30 lm/W	
MODEL	KL-3360	Imax(cd)	650.9	S/MH(C0/180)	1.22
NOMINAL POWER(W)	18	LOR(%)	84.0	S/MH(C90/270)	1.21
RATED VOLTAGE(V)	230	TOTAL FLUX(lm)	1755.5	η UP,DN(C0-180)	0.0,42.6
NOMINAL FLUX(lm)	2090.5	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,41.4
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	230	η down(%)	84.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE(50%):106.9 DEG

C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



K-LITE

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:K-LITE
Test Date:17 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity:65.0%
Test Distance:1.852m [K=1.0000]
Remarks: