


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.66V I:0.0780A P:17.615W PF:0.9796 Freq:49.99Hz Lamp Flux:2304x1 lm		
NAME: QUAD MINI	TYPE:CEILING LUMINAIRES	WEIGHT:
SPEC.:NW, CITIZEN, BA-25°	DIM.: Sq 106 x 150	SERIAL No.:5178
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-3645	Imax (cd)	8085	S/MH (C0/180)	0.36
NOMINAL POWER (W)	18	LOR (%)	80.2	S/MH (C90/270)	0.35
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	1847.8	η UP, DN (C0-180)	0.0, 42.2
NOMINAL FLUX (lm)	2304	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 38.0
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	230	η down (%)	80.2	CIBSE SHR MAX	1.00



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 23 November 2022

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.852m [K=1.0000]
Remarks: