



STREETLIGHT PHOTOMETRIC TEST REPORT

Test:U:230.37V I:0.4124A P:94.734W PF:0.9972 Freq:49.99Hz Lamp Flux:12593.6x1 lm		
NAME: AVENUE 100	TYPE:POLE MOUNTED SYSTEMS	WEIGHT:3.345Kg
SPEC.:3000K, LUMILED, 70 CRI	DIM.: 526 x 174 x 90	SERIAL No.:INT/2023/08/62B
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 127.61 lm/W
MODEL	KL-4392	I _{max} (cd)	9351	η street_up (%)	0.0	
NOMINAL POWER (W)	100	LOR (%)	96.0	η street_down (%)	78.0	
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	12089	η house_up (%)	0.0	
NOMINAL FLUX (lm)	12593.6	MAXIMUM @ (C, γ)	30, 63.0	η house_down (%)	18.0	
LAMPS INSIDE	1	η up (%)	0.0	76 FLASHAREA (m2)	0.00100	
TEST VOLTAGE (V)	230	η down (%)	96.0	SLI	18.016	



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 14 August 2023

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 45.4%
Test Distance: 1.944m [K=1.0000]
Remarks: