



STREETLIGHT PHOTOMETRIC TEST REPORT

Test:U:230.54V I:0.2236A P:50.546W PF:0.9807 Freq:49.99Hz Lamp Flux:7027.5x1 lm		
NAME: NAVIRA MINI	TYPE:WALL LUMINAIRES	WEIGHT:
SPEC.:WW, LUMILED,TYPE IV	DIM.: 220 x 170 x 260	SERIAL No.:5299 A
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 125.87 lm/W			
MODEL	KL-4444	Imax(cd)	3548	η street_up(%)	0.2
NOMINAL POWER(W)	50	LOR(%)	90.5	η street_down(%)	72.1
RATED VOLTAGE(V)	230	TOTAL FLUX(lm)	6362	η house_up(%)	0.2
NOMINAL FLUX(lm)	7027.5	MAXIMUM @ (C, γ)	50, 66.0	η house_down(%)	18.1
LAMPS INSIDE	1	η up(%)	0.4	76 FLASHAREA(m2)	0.00100
TEST VOLTAGE(V)	230	η down(%)	90.2	SLI	15.419



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 24 January 2023

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 26.000m [K=1.0000]
Remarks: