



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.15V I:0.0261A P:5.9146W PF:0.9852 Freq:50.00Hz Lamp Flux:683.385x1 lm		
NAME: TRIOSCAPE - BRACKET	TYPE:FLOOD LIGHTS	WEIGHT:0.470 Kg
SPEC.:2700K, LUMILED, BA-25°, CRI 70	DIM.: 83 x 116 x 110	SERIAL No.:INT/2024/05/86B
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 82.16 lm/W
MODEL	KL-7057	I _{max} (cd)	2400	S/MH (C0/180)	0.39	
NOMINAL POWER (W)	6	LOR (%)	71.1	S/MH (C90/270)	0.35	
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	485.96	η UP, DN (C0-180)	0.0, 35.4	
NOMINAL FLUX (lm)	683.385	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 35.7	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00	
TEST VOLTAGE (V)	230	η down (%)	71.1	CIBSE SHR MAX	1.00	



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.7DEG
Operators: K-LITE
Test Date: 22 July 2024

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 44.4%
Test Distance: 2.001m [K=1.0000]
Remarks:
APPLICABLE ID - KL-7052