K-LiTE

Beacon Metro Mega 2.0

An elegant and efficient post top luminaire with translucent diffuser provide a unique, comfortable light choice with symmetrical and glare free light distribution. Aesthetically designed sturdy construction ensures a long life against all weather condition, maintaining initial performances through the lifetime of the installation.



Product Description

- The luminaire comprises of spun & die-cast aluminium.
- Spun aluminium reflector system encased in translucent UV protected polycarbonate diffuser for rotationally symmetrical distribution of light.
- Luminaire integrated with 30W LED.
- Suitable for mounting on 76mm OD pipe.
- Cable entries for through-wiring of mains supply cable.
- Integral constant current power supply
- CRI (Ra) : >70
- Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply.
- Ordering guide : KL-22793-CCT (Colour Temperature)
- Available CCT : 2700K, 3000K, 4000K, 5700K

IP66

Product Benefits

- Elegant, Functionality
- Environmental Friendly
- Dark sky compliant protects pedestrians from glare, in addition to preventing spill light above the horizontal plane.
- Sustainable LED technology offers durability and optimal light output with low power consumption.

Area of Application

Illuminating parks, Gardens, commercial complex, Residential roadways, Walkways, Streetscapes & office complex.

Available Finish

Pure polyester powder coated

RAL 9004 Black

RAL 7016 Anthracite grey

Graphite grey

K-LITE

Beacon Metro Mega 2.0





Technical Specifications

General

ID	: 22793
System Wattage	: 30W LED
Driver Integral	: Constant Current
Operating Voltage	: 100-277Vac
Operating Temperature	: -15°C~+50°C

Physical

Body	: Spun & Die Cast Aluminium
Diffuser	: Translucent Polycarbonate
Mounting	: Suitable for Mounting on Ø76mm OD Pipe
Finish	: Powder coated RAL 9004 Black RAL 7016 Anthracite grey Graphite grey

Light Source


Light Source	: LUMILEDS
CRI (Ra)	: >70
LED Colour Temperature	: 2700K / 3000K / 4000K 5700K

Driver

Power Supply	: Integral
Input Voltage	: 230-240Vac
Frequency	: 50-60Hz
Power Factor	: >0.95
THD	: <10%
Surge Protection	: 4KV
Efficiency	: >87%

Optical Performance

Light Distribution	: Symmetrical



IP66

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at **www.klite.in**