K-LiTE

Juno

This elegant lantern features a translucent diffuser that delivers a soft, glare-free light, creating a comfortable and inviting atmosphere. Its thoughtfully designed, robust construction ensures long-lasting performance, even in harsh weather conditions. With its enduring durability and consistent light output, this lantern maintains its initial quality throughout its lifespan, offering a reliable and stylish lighting solution for any environment.



Product Description

- Aluminium housing, integrated with extruded aluminium pipe along with pressure die cast aluminium base through supporting arms made of gravity die cast aluminium.
- Diffuser placed into the provision formed on the pheriphery of the bottom cover.
- Non yellowing UV stabilized translucent acrylic diffuser.
- Low power loss LED driver with 60W LED.
- Suitable for mounting on 60mm OD pipe.
- Cable entries for through-wiring of mains supply cable.
- Integral constant current power supply
- CRI (Ra) : ≥80
- Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply.
- Ordering guide : KL-25040-CCT (Colour Temperature)
- Available CCT : 2700K, 3000K, 4000K, 5700K

IP65 IK07

Product Benefits

- Elegance, Functionality.
- Environmental friendly, moisture proof, insect free.
- Dark sky compliant protects pedestrians from glare, in addition to preventing spill light above the horizontal plane.
- Sustainable LED technology offers durability and optimal light output with low power consumption.

Area of Application

Illuminating parks, Gardens, commercial complex, Pathways in residential buildings & office complex.

Available Finish

Pure polyester powder coated


RAL 9004 Black

RAL 7016 Anthracite grey

Graphite grey

K-LITE

Juno





JAIPUR CHAUPATI

Technical Specifications

General

ID	: 25040
System Wattage	: 60W LED
Driver Integral	: Constant Current
Operating Voltage	: 100-277Vac
Operating Temperature	: -15°C~+50°C

Physical

Body	: Extruded aluminium with Spun Aluminium Top
Diffuser	: Translucent Acrylic
Mounting	: Suitable for Mounting on Ø60mm OD Pipe
Finish	: Powder coated RAL 9004 Black RAL 7016 Anthracite grey Graphite grey

Light Source


Light Source	: NICHIA
CRI (Ra)	: >80
LED Colour Temperature	: 2700K / 3000K / 4000K 5700K

Driver

Power Supply	: Integral
Input Voltage	: 230-240Vac
Frequency	: 50-60 Hz
Power Factor	: >0.95
THD	: <10%
Surge Protection	: 6KV
Efficiency	: >88%

Optical Performance

Light Distribution	: 120°



IP65 IK07

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at **www.klite.in**