



ABHIJEET FERRO ALLOYS (TEMPLE LIGHTING), AP

Technical Specifications

General

ID	: 22561
System Wattage	: 30W / 50W / 60W 60W RGBW
Driver Integral	: Constant Current
Operating Voltage	: 100-300Vac
Operating Temperature	: -15°C~+50°C

Physical

Body	: Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser	: Polycarbonate Optical Lens
Mounting	: Surface / Wall
Finish	: Powder coated RAL 9004 Black RAL 9007 Grey aluminium RAL 7016 Anthracite grey Graphite grey

Light Source

Light Source	: NICHIA
CRI (Ra)	: >80
LED Colour Temperature	: 2700K / 3000K / 4000K 5700K / RGBW

Driver


Power Supply	: Integral
Input Voltage	: 230-240Vac
Frequency	: 50-60Hz
Power Factor	: >0.95
THD	: <10%
Surge Protection	: 4KV / 6KV
Efficiency	: >85%
Dimmable Option	: Analog / Dali
Control	: RGBW Compatibility

Optical Performance





Beam Angle	: 10° / 28° / 45°
------------	-------------------



Surface Mount



Wall Mount



150° Rotatable



Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in