



OPEN SOURCE



Technical Specifications

General

|                       |                    |
|-----------------------|--------------------|
| ID                    | : 24320            |
| System Wattage        | : 40W LED          |
| Driver Non-Integral   | : Constant Voltage |
| Operating Voltage     | : 24Vdc            |
| Operating Temperature | : -30°C~+50°C      |

Physical

|          |                                           |
|----------|-------------------------------------------|
| Body     | : 6063 Aluminium Alloy                    |
| Diffuser | : Clear Toughened Glass                   |
| Mounting | : Surface - Bracket                       |
| Finish   | : Powder Coated<br>RAL 7024 Graphite Grey |

Light Source

|                        |                                            |
|------------------------|--------------------------------------------|
| Light Source           | : OSRAM                                    |
| CRI (Ra)               | : >80                                      |
| LED Colour Temperature | : 3000K / RGBW<br>(Other CCT's on request) |

Driver

|                        |                                  |
|------------------------|----------------------------------|
| Power Supply           | : Non Integral                   |
| THD                    | : <5%                            |
| Protection             | : Flicker Free, OVP, SCP,OLP,OTP |
| Control Options        | : ON/OFF / Dali                  |
| Control for RGBW /RGBA | : DMX512 compatible              |

Optical Performance

|            |                     |
|------------|---------------------|
| Beam Angle | : 2° / 20°/ 10°x30° |
|------------|---------------------|

§

CE

IP66

IK05

50,000 h  
L70 B10

SDCM  
≤ 3

