K-LiTE Cyrilla

Surface-mounted range of wall lights are a great solution for a variety of outdoor lighting needs. These fixtures are specifically designed to provide focused illumination on the wall and the area directly in front of it. They are ideal for accentuating vertical surfaces such as building facades, garden walls, and outdoor structures. Whether used to create ambiance or to enhance security with bright, focused light, these lights can serve multiple purposes in outdoor environments.

### **Product Description**

- Luminaire top cover & bottom frame made of pressure die-cast aluminium with extruded aluminium alloy (grade 6063) supporting arm.
- Translucent polycarbonate diffuser.
- · Luminaire integrated with 12W LED.
- · Aluminium base for easy installation onto the wall.
- Surface mounting on wall using hardware after connecting to the power supply.
- · Cable entries for through-wiring of mains supply cable
- · Integral constant current power supply
- CRI (Ra): ≥80
- Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply.
- Ordering guide: KL-24336-CCT (Colour Temperature)
- Available CCT: 2700K, 3000K, 4000K, 6500K









### **Product Benefits**

- Sturdy construction in order to maintain performance of the luminaire and to reduce maintenance costs.
- Quick & simple installation with low maintenance.
- The diffuser contributes to the creation of ambiance and to visual comfort by reducing glare.
- Sustainable LED technology offers durability and optimal light output with low power consumption.

## Area of Application

Residential, Building facade, Commercial centres, Passages, Pathways.

## Available Finish

Pure polyester powder coated RAL 9004 Black RAL 9007 Grey aluminium RAL 7016 Anthracite grey Graphite grey



K-LiTE Cyrilla





# **Technical Specifications** General

ID : 24336 : 12W LED System Wattage Driver Integral : Constant Current Operating Voltage : 100-277Vac

Operating Temperature

Physical

Body : Die-Cast Aluminium Arm : Extruded Aluminium : Translucent Polycarbonate Power Factor Diffuser Mounting : Surface - Wall Finish

: Powder coated RAL 9004 Black RAL 9007 Grey aluminium

RAL 7016 Anthracite grey

Graphite grey

:-15°C~+50°C

Light Source

Light Source : CITIZEN COB : >80

CRI (Ra)

LED Colour Temperature : 2700K / 3000K / 4000K /


6500K

Driver

Power Supply : Integral Input Voltage : 230-240Vac Frequency : 50-60Hz :>0.95 : <10% Surge Protection : 4KV Efficiency :>80%

Optical Performance

Light Distribution : Symmetrical














Note: It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in