



leva-1

The surface-mounted LED luminaries are ideal for wall, ceiling, and floor applications. They seamlessly integrate with commercial, historical, and modern architectural styles, enhancing the aesthetic appeal of any space.

MATERIAL

Body : Die cast aluminium alloy
Impact Protection : IK06
Ingress Protection : IP66
Diffuser : Clear Tempered Glass
Mounting : Surface - Bracket

ELECTRICAL

Driver : Constant Voltage
Power Supply : Non-Integral
Operating Voltage : 24Vdc

PRODUCT CONFIGURATIONS

Wattage : 6W
CCT : 3000K
LED Life Time : L70 B10 50,000 H

AREA OF APPLICATION

Building Facade, Architectural focal points, Architectural elements.

AVAILABLE FINISH

Pure polyester powder coated grey



Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in



Technical Specifications

General

ID	: 4466
System Wattage	: 6W LED
Driver Non-Integral	: Constant Voltage
Operating Voltage	: 24Vdc
Operating Temperature	: -10°C~+50°C

Light Source

Light Source	: OSRAM
CRI (Ra)	: >80
LED Colour Temperature	: 3000K

Physical

Body	: Die Cast Aluminium Alloy
Diffuser	: Clear Tempered Glass
Mounting	: Surface - Bracket
Finish	: Grey

Driver

Power Supply	: Non Integral
--------------	----------------

Optical Performance

Beam Angle	: 2°
------------	------

