

Technical Specifications

General

| | |
|-----------------------|--------------------|
| ID | : 4391 |
| System Wattage | : Upto 40W LED |
| Driver Integral | : Constant Current |
| Input Voltage | : 230-240Vac |
| Frequency | : 50Hz |
| Operating Voltage | : 100-270Vac |
| Operating Temperature | : -15°C~+50°C |

Physical

| | |
|----------|---|
| Body | : Die Cast Aluminium |
| Diffuser | : Clear Toughened Glass |
| Mounting | : Suitable for Mounting on 38mm OD pipe |
| Finish | : Powder coated Graphite grey Anthracite grey / Jet black |

Light Source


| | |
|------------------------|-------------------------|
| Light Source | : LUMILED / Equivalent |
| CRI (Ra) | : ≥70 (>80 On Request) |
| LED Colour Temperature | : 3000K / 4000K / 5700K |

Driver

| | |
|------------------|------------|
| Power Supply | : Integral |
| Power Factor | : >0.97 |
| THD | : <10% |
| Surge Protection | : 4KV |
| Efficiency | : >85% |

Optical Performance

| | |
|---|------------------------------|
| Colour Temperature | : 3000K |
| Luminous flux | : 4476 lm, 4503 lm, 4657 lm |
| Optical Distribution | : Type II, Type III, Type IV |
| For other IES files - Please refer Online | |



Note : • Luminous flux / Power consumption may vary by ±10%.
• Luminaire efficiency upto 130 lm/W.

Photometric Data

